




CDU 700 SERIES UNIBUS SCSI HOST ADAPTER



The CMD's CDU-700 Unibus SCSI host adapter is the best solution to bridging DEC MSCP/TMSCP protocols and SCSI optical, magnetic disk and tape products.

- 16-bit microprocessor
- Unibus MSCP, TMSCP compatible
- 16 KB sector buffer
- Command queuing and seek optimization
- Support up to 7 SCSI devices
- SCSI bus transfer rate up to 2 MB/sec
- Support disconnect and reconnect capability
- Support magnetic disk, tape and optical drives
- On-board utility to format, qualify drives
- Automatic drive configuration
- Dynamic defect management
- ANSI compatible tape format
- User selectable auto bootstrap

For more information or to order call:

1-800-4-CMD-TEC

(1-800-426-3832)

In California call: (714) 454-0800



1 Vanderbilt
Irvine, California 92718
(714) 454-0800 • FAX: (714) 455-1656

CMD TECHNOLOGY, INC. ANNOUNCES: CDU-700 UNIBUS SCSI HOST ADAPTER.

The CDU-700 is an intelligent Unibus SCSI host adapter which is fully compatible with the DEC Mass Storage Control Protocol (MSCP) and Tape Mass Storage Control Protocol (TMSCP).

The CDU-700 can be used with the PDP-11/84, PDP-11/70, PDP-11/44, PDP-11/34, PDP-11/24, VAX, etc. It supports RT-11, TSX +, RSX, RSTS, ULTRIX, UNIX, VMS and other operating systems which use the DU/MU drivers.

The CDU-700 supports 16K bytes sector buffer, command queuing, seek optimization, standard SCSI bus arbitration, disconnect/reconnect, and all required SCSI commands. Up to seven SCSI target devices (magnetic or optical) can be connected to CDU-700 with SCSI bus data transfer rate to 2M bytes per second.

The CDU-700 has an on-board utility for users to configure and format drives, scan bad blocks and replace them automatically.

The CDU-700 contains a user selectable automatic bootstrap option which can boot up the system on power up. It comes standard with an installation manual and a one year warranty.

CONTROLLER SPECIFICATIONS

Emulation: MSCP, TMSCP

Bus Interface: Unibus

CSR address: (Disk) 772150, 760334, 760354, 760374,
760340, 760344, 760350, 760360
(Tape) 774500, 760404, 760444, 760504,
760544, 760410, 760450, 760454
(Disk/Tape) 772150, 760334, 760354, 774500,
760404, 760444

Interrupt priority: Level 4

Interrupt vector: Software programmable

Command queuing: 10 commands with optimized seek

Data buffer capacity: 16K-Byte sector buffer

Bootstrap: On board auto bootstrap and utility bootstrap

Formatting: On board format and bad block replacement

Software supported: All standard DEC operating systems

LED Indicators: Self test, drive error

Peripheral interface: Small Computer System Interface
(SCSI)

SCSI bus transfer rate: 2MB/sec (maximum)

SCSI parity: Odd parity

Multiple device support: Up to 7 SCSI devices

System performance: Support disconnect/reconnect
capability

SCSI Driver/Receiver: Single ended

SCSI cable length: Up to 20 ft. (6 m)

Operating temperature: 5°C to 50°C

Relative humidity: 10% to 90%, non-condensing

Power requirement: 5VDC, 2.8A

MODEL DESCRIPTION

CDU-700/M Magnetic disk

CDU-700/T Magnetic tape

CDU-700/OM . . . Optical and magnetic disk

CDU-700/TM . . . Magnetic disk and tape

DRIVES SUPPORTED:

DISK:

CDC, C.itoh, Conner, Fujitsu, Hitachi, Maxtor, Micropolis,
Priam, Quantum, Rodime, Seagate, Siemens, Toshiba, ... etc.

TAPE:

Cipher, Exabyte, Wangtek, Kennedy, Archive, Caliper,
Tandberg, Fujitsu, CDC, DAT, ... etc.

ERASABLE OPTICAL:

Ricoh, Sony, ... etc.

CD-ROM:

LMS, Phillips, Toshiba, ... etc.

* MSCP, TMSCP, RT-11, RSX, ULTRIX, RSTS, VMS, Unibus, PDP-11, VAX are trademarks of Digital Equipment Corporation

* TSX + is a trademark of S & H Computer Systems, Inc.

* UNIX is a trademark of AT&T

* Specifications subject to change without notice



1 Vanderbilt • Irvine, California 92718
(800) 426-3832 • (714) 454-0800 • FAX: (714) 455-1656